



- NOTES:
- 1. SPECIFICATIONS PER IDS-156.
  - 2. IMPEDANCE: 50 Ohms.
  - 3. FREQUENCY: DC UP TO 67 GHz.
  - 4. HI-POT & CONTINUITY TEST 100%.
  - 5. HOUSING: PX16, PRX AND CUSTOM HOUSINGS, SIZE 16 CAVITY.

PHOENIX P/N	LEN. - "L" (in)	LEN. - "L" (mm)
1560000EK001006	6.00 ±0.25	(152.4 ±6.4)
1560000EK001012	12.00 ±0.50	(304.8 ±12.7)
1560000EK001024	24.00 ±0.75	(609.6 ±19.1)
1560000EK001036	36.00 ±1.00	(914.4 ±25.4)
1560000EK001039	39.00 ±1.13	(990.6 ±28.7)
1560000EK001048	48.00 ±1.25	(1219.2 ±31.8)
1560000EK001060	60.00 ±1.50	(1524.0 ±38.1)
1560000EK001096	96.00 ±2.25	(2438.4 ±57.2)

A	RELEASE PER ECN 14495	5/22/2025	KKC
01	PRELIMINARY	4/29/2025	KKC
REV	DESCRIPTION	DATE	APPROVAL

This drawing embodies a proprietary design of The Phoenix Company of Chicago, Inc., Naugatuck, CT 06770. All design, manufacturing, reproduction, use, sale, and other rights regarding the same are expressly reserved. The information in this drawing may be covered completely or in part by patents and/or patents pending.

WARNING - THIS DOCUMENT CONTAINS TECHNICAL DATA WHOSE EXPORT IS RESTRICTED BY THE ARMS EXPORT CONTROL ACT (TITLE 22, U.S.C., SEC 2751, ET. SEQ.) OR THE EXPORT ADMINISTRATION ACT OF 1979, AS AMENDED, TITLE 50, U.S.C., APP 2401 ET SEQ. VIOLATIONS OF THESE EXPORT LAWS ARE SUBJECT TO SEVERE CRIMINAL PENALTIES. DISSEMINATE IN ACCORDANCE WITH PROVISIONS OF DOD DIRECTIVE 5230.25.

UNLESS OTHERWISE SPECIFIED, PHOENIX WORKMANSHIP STANDARDS APPLY DIMENSIONS IN INCHES OR [METRIC]	APPROVALS	DATE
DO NOT SCALE PRINTS  TOLERANCES ARE: FRACTIONS: ± 1/64 DECIMALS: .XX ± .01 .XXX ± .003 ANGLES: ± 1/2°	DRAWN KKC	4/29/2025
	CHECKED DRW	5/22/2025
	QA JK	5/22/2025
	MFG VL	5/22/2025
	ENGINEER SJG	5/22/2025
APPROVED KKC	5/22/2025	

**The PHOENIX Company of Chicago, Inc.**  
22 GREAT HILL RD., NAUGATUCK, CT 06770  
WWW.PHOENIXOFCHICAGO.COM  
PHONE: (800) 323-9562 FAX:(630) 206-1801

TITLE  
**SIZE 16 PkZ® RECEPTACLE CABLE ASSEMBLY, .047, BLUNT-CUT END**

SIZE B	FSCM 58167	DWG NO <b>1560000EK001XXX</b>	REV A	PLATING OPT.
SCALE 2 : 1		F.S.R. #	SHEET 1 OF 1	