



<u>CABLE</u>

PKZ ASSEMBLY






В


Step 1 (for Flex style cable only) Dip end of cable into flux and then tip dip cable to $.30\pm.02$ into solder pot for 3 second max.

Step 2
Trim cable to dimensions shown,
(.285±.010 dimension for jacketed cables only). Point center conductor.
Check center conductor for straightness.





Step 3 Install cable into body until cable bottoms in body. Solder body to cable as shown. Clean solder joint.



Α

CAD DRAWING - NO MANUAL REVISIONS

WARNING - THIS DOCUMENT CONTAINS TECHNICAL DATA WHOSE EXPORT IS RESTRICTED BY THE ARMS EXPORT CONTROL ACT (TITLE 22, U.S.C., SEC 2751, ET. SEQ.) OR THE EXPORT ADMINISTRATION ACT OF 1979, AS AMENDED, TITLE 50, U.S.C., APP 2401 ET SEQ. VIOLATIONS OF THESE EXPORT LAWS ARE SUBJECT TO SEVERE CRIMINAL PENALTIES. DISSEMINATE IN ACCORDANCE WITH PROVISIONS OF DOD DIRECTIVE 5230.25.

MATERIAL:							The $PHOENIX$ Company of Chicago			
				UNLESS OTHERWISE SPECIFIED, PHOENIX WORKMANSHIP STANDARDS APPLY DIMENSIONS IN INCHES OR (METRIC) DO NOT SCALE PRINTS	APPROVALS DRAWN JEM	DATE 08/10/15	22 GREAT HILL RD., NAUGATUCK, CT 06770 WWW.PHOENIXOFCHICAGO.COM			
				TOLERANCES ARE: FRACTIONS: ± 1/64 DECIMALS: .XX ± .01 32	CHECKED R.M.B	08/10/15	TITLE	WW.PHOENIXOFCH	ICAGO.CON	
G	PER ECN 13349	6/11/2019	JEM	.XXX ± .003 V ANGLES: ± 1/2'	QA		CABLE ASSEMBLY PROCESS			
F	PER ECN 13163	10/26/2018	JEM							
E	PER ECN 12707	11/21/2017	JEM	THE INFORMATION DISCLOSED IN	MFG		FOR 168-0020-0860			
D	PER ECN 12668	10/12/2017	SPS	THIS DOCUMENT IS CONFIDENTIAL			101(100 0020 0000			
С	PER ECN 12294	3/15/2016	RMB		ENGINEER JEM	08/10/15	SIZE FSCM DWG	NO	REV	PLATING OPT.
В	PER ECN 12240	10/28/2015	RMB	AND MAY NOT BE USED FOR MANUFACTURE OR ANY OTHER PURPOSE WITHOUT THE WRITTEN CONSENT OF THE PHOENIX CO. OF					G	
Α	REL. PER ECN 12197	8/12/2015	RMB		R.M.B	08/10/15	A 58167 10	168-0020-0860		
REV.	DESCRIPTION	DATE	APPR.	CHICAGO INC.			SCALE F	.S.R. #	SHEET 1	OF 1

2

4

1