

 $\mathbf{\Phi}$

2

3

В

₽

4

	NOTES: 1. SPECIFICATIONS PER IDS-26. 2. ACCOMMODATES RG-402 (.141 SEMI-RIGID) OR EQUIVALENT FLEXIBLE CABLE. HOUSING: DIN 41612, SIZE 8 CAVITY.						PART NUMBER 26D-0020-1410 26D-0021-1410 26D-0023-1410 26D-0025-1410	O-RING OPTIONS NONE ENVIRONMENTAL EMI SPRING GROUNDING RING	
А		C ECN 6253 9/10/01 HN		TO SEVERE CRIMINAL PENALTIES. DISSEMINATE IN	DO NOT SCALE PRINTS TOLERANCES ARE: FRACTIONS: ± 1/64 DECIMALS: .XX ± .01 .XXX ± .003	APPROVALSDATEDRAWN MY11/10/1995CHECKED HN11/10/1995QA	TITLE PKZ [®] PLUG, DIRECT SOLDER TERMINATION		A
	SCALE 2.5 : 1 4	B ECN 4374 2/10/98 HN A ECN 3206 11/10/95 HN REV. DESCRIPTION DATE BY 3			ANGLES: ± 1/2' 32√- 2	MS 11/10/1995 APPROVED HN 11/10/1995	B 58167 26-0020- SCALE 4:1 F.S.R. #	1410 C A, B, C, D SHEET 1 OF 1	

В

4