



NOTES:
1. SPECIFICATIONS PER IDS-556.
2. EXTENDED SOLDER NUT SHIPPED LOOSE.
3. ACCOMMODATES RG405 S/R, TFLEX405, SS405, IW1251, IW1151 OR EQUIVALENT CABLE.
4. MECHANICAL RESULTS WHEN MATED TO 556 SERIES SIZE 12 PkZ PLUG (PIN) CONTACTS ONLY:
   a) MATING CYCLES: > 50,000.
5. ELECTRICAL RESULTS WHEN MATED TO 556 SERIES SIZE 12 PkZ PLUG (PIN) CONTACTS ONLY:
   a) FREQUENCY: DC TO 50 GHz.
   b) VSWR: 1.50 : 1 MAX.
6. HOUSING: PX AND CUSTOM, SIZE 12 CAVITY**.**
7. DOES NOT MATE WITH OTHER INDUSTRY-STANDARD SIZE 12 CONTACTS.



SCALE 2.5 : 1

REV.	DESCRIPTION	BY	DATE
A	REL. PER ECN 14573	SPS	10/29/2025

THE INFORMATION AND DESIGNS DISCLOSED IN THIS DOCUMENT ARE CONFIDENTIAL AND/OR PROPRIETARY TO THE PHOENIX COMPANY OF CHICAGO INC. AND MAY NOT BE USED FOR MANUFACTURING, REPRODUCED, DISCLOSED TO OTHERS OR FOR ANY OTHER PURPOSE WITHOUT THE EXPRESS WRITTEN CONSENT OF THE PHOENIX COMPANY OF CHICAGO INC.

WARNING - THIS DOCUMENT CONTAINS TECHNICAL DATA WHOSE EXPORT IS RESTRICTED BY THE ARMS EXPORT CONTROL ACT (TITLE 22, U.S.C., SEC 2751, ET. SEQ.) OR THE EXPORT ADMINISTRATION ACT OF 1979, AS AMENDED, TITLE 50, U.S.C., APP 2401 ET SEQ. VIOLATIONS OF THESE EXPORT LAWS ARE SUBJECT TO SEVERE CRIMINAL PENALTIES. DISSEMINATE IN ACCORDANCE WITH PROVISIONS OF DOD DIRECTIVE 5230.25.

UNLESS OTHERWISE SPECIFIED, PHOENIX WORKMANSHIP STANDARDS APPLY
DIMENSIONS IN INCHES OR [METRIC]

DO NOT SCALE PRINTS

TOLERANCES ARE:
FRACTIONS: ± 1/64
DECIMALS: .XX ± .01
.XXX ± .003
ANGLES: ± 1/2˚

$\sqrt{32}$

APPROVALS	DATE
DRAWN SPS	10/29/2025
CHECKED SJG	10/29/2025
QA	
MFG	
ENGINEER SPS	10/29/2025
APPROVED SJG	10/29/2025

The PHOENIX Company of Chicago, Inc.
22 GREAT HILL RD., NAUGATUCK, CT 06770
WWW.PHOENIXOFCHICAGO.COM
PHONE: (800) 323-9562 FAX:(630) 206-1801

TITLE: SIZE 12 PkZ® RECEPTACLE (SOCKET) CONTACT, HIGH MATING LIFE, EXTENDED SOLDER NUT TERMINATION

SIZE	FSCM	DWG NO	REV	PLATING OPT.
B	58167	**556-1030-0861**	A	A, C

SCALE	F.S.R. #	SHEET
5 : 1		1 OF 1