



STEP 1

***FOR FLEX CABLES: (Jacketed)**
 Flux and Tin Dip Cable to dimension - $.400 \pm .010$
(LEAD FREE SOLDER RECOMMENDED)
 Trim Jacket to dimension - $.380 \pm .010$
 Trim for Center Conductor to dimension - $.105 \pm .005$
 Point the Center Conductor.



STEP 2

Insert Cable into Body until the cable bottoms and then solder. Clean solder joint.
(LEAD FREE SOLDER RECOMMENDED)



WARNING - THIS DOCUMENT CONTAINS TECHNICAL DATA WHOSE EXPORT IS RESTRICTED BY THE ARMS EXPORT CONTROL ACT (TITLE 22, U.S.C., SEC 2751, ET. SEQ.) OR THE EXPORT ADMINISTRATION ACT OF 1979, AS AMENDED, TITLE 50, U.S.C., APP 2401 ET SEQ. VIOLATIONS OF THESE EXPORT LAWS ARE SUBJECT TO SEVERE CRIMINAL PENALTIES. DISSEMINATE IN ACCORDANCE WITH PROVISIONS OF DOD DIRECTIVE 5230.25.

The information and designs disclosed in this document are confidential and/or proprietary to The Phoenix Company of Chicago, Inc. and may not be used for manufacturing, reproduced, disclosed to others, or used for any other purpose without express written consent of The Phoenix Company of Chicago, Inc.

MATERIAL:

UNLESS OTHERWISE SPECIFIED, PHOENIX WORKMANSHIP STANDARDS APPLY. DIMENSIONS IN INCHES OR [METRIC].					
DO NOT SCALE PRINTS					
TOLERANCES ARE: FRACTIONS: $\pm 1/64$ DECIMALS: $.XX \pm .01$ $.XXX \pm .003$ ANGLES: $\pm 1/2^\circ$					
A	REL. PER ECN 14507	SPS	10/2/2025	SJG	10/2/2025
01	PRELIMINARY	SPS	9/24/2024	SJG	9/24/2024
REV.	DESCRIPTION	BY	DATE	APPR.	DATE

APPROVALS	DATE
DRAWN SPS	10/10/2024
CHECKED SJG	10/10/2024
QA	
MFG	
ENGINEER SPS	10/10/2024
APPROVED SJG	9/24/2024

The PHOENIX Company of Chicago, Inc.
 22 GREAT HILL RD., NAUGATUCK, CT 06770
 WWW.PHOENIXOFCHICAGO.COM
 PHONE: (800) 323-9562 FAX: (630) 206-1801

TITLE
CABLE ASSEMBLY PROCEDURE FOR 65-1020-1911

SIZE	FSCM	DWG NO	REV	PLATING OPT.
A	58167	65-1020-1911	A	
SCALE	4 : 1		F.S.R. #	11836
SHEET			1	OF 1