INTERFACE DESIGN STANDARD	
IDS-10J-RIGHT ANGLE	
SHEET 1 OF 1	DATE: 8/24/06
DRAWN: EK	APPROVED: JEM

The PHOENIX Company of Chicago, Inc.
22 GREAT HILL RD., NAUGATUCK, CT 06770
WWW.PHOENIXOFCHICAGO.COM

PHONE: (800) 323-9562 FAX: (630) 206-1801

REV.	DESCRIPTION	DATE	APPR.
C	PER ECN 12823	04/02/18	JEM
D	PER ECN 13001	6/21/18	JEM
E	PER ECN 13033	7/23/18	JEM
F	PER ECN 14215	11/26/24	DW

Description: 10J Series, SMC, Non-Magnetic Right Angle Connector

MATERIALS

BODIES

Plug: Non-Magnetic Brass
Receptacle: Non-Magnetic Brass

CONTACTS

Male Contact: Non-Magnetic Brass Or Beryllium Copper Per ASTM B196
Female Contact: Beryllium Copper Per ASTM B196

Residual Magnetism < 1.0000 mu

INSULATORS

Virgin Teflon (PTFE) Per ASTM D1710

PLATING

Gold Per MIL-DTL-45204 (Electro Deposited)
Copper Per SAE AMS 2418 (Electro Deposited)

FINISH (Ending Letter of Part Number)

Bodies:	.000020" Min. Gold Over Copper
Contacts:	.000030" Min. Gold Over Copper
Other Metal Parts:	Gold Plated To Meet The Environmental Requirements

MATING CHARACTERISTICS

Center Contacts:	40 oz. (2.5 lbs.) Max. Insertion 1 oz. (0.063 lbs.) Min. Withdrawal Per MIL-C-39012
Engagement/ Disengagement Force:	16 in.-oz. (1 lbs.) Max. Torque
Mating Torque:	35-50 in.-oz. (2.188-3.125 in.-lbs.) Coupling Nut Proof Torque: 100 in.-oz. (6.25 in.-lbs.) 560 oz. Coupling Nut Retention Force: 560 oz. (35 lbs.) Min.

ELECTRICAL

Frequency Range:	DC To 10 GHz
Voltage Rating Straight:	335 VRMS
Insulation Resistance:	1000 Megohms Min.
Insertion Loss:	0.6dB Max. 1.5 (GHz)
Impedance:	50 Ohms
Contact Resistance:	12.0 Milliohms

VSWR:	RG-178 Or Equivalent 1.45 + .04*f (GHz) RG-316 Or Equivalent 1.35 + .04*f (GHz)
DWV:	RG-178 Or Equivalent 500 VRMS RG-316 Or Equivalent 700 VRMS
Corona Level:	70,000 ft.- 185 Volts (RG-178), 250 Volts (RG-316)
RF Leakage:	-55 dB Min. @ 2-3 GHz

ENVIRONMENTAL

Operating Temperature:	-65°C To +165°C
Vibration:	MIL-STD-202, Method 204, Test Condition D
Shock:	MIL-STD-202, Method 213, Test Condition A
Thermal Shock:	MIL-STD-202, Method 107, Test Condition C
Durability:	500 Cycles
Corrosion:	MIL-STD-202, Method 101, Test Condition B
Moisture Resistance:	MIL-STD-202, Method 106

WARNING - THIS DOCUMENT CONTAINS TECHNICAL DATA WHOSE EXPORT IS RESTRICTED BY THE ARMS EXPORT CONTROL ACT (TITLE 22, U.S.C., SEC 2751, ET. SEQ.) OR THE EXPORT ADMINISTRATION ACT OF 1979, AS AMENDED, TITLE 50, U.S.C., APP 2401 ET SEQ. VIOLATIONS OF THESE EXPORT LAWS ARE SUBJECT TO SEVERE CRIMINAL PENALTIES. DISSEMINATE IN ACCORDANCE WITH PROVISIONS OF DOD DIRECTIVE 5230.25.