	4	1		3	4	
D	c) GUIDE PINS: STAINLESS 3. FINISHES: a) HOUSING: NONE. b) HARDWARE: PASSIVAT	TE: ACETAL, COLOR: BLA WS, JACKSCREW HEADS AND WASHERS): STAINL STEEL.	CK. , SCREWS <i>,</i>			
	c) GUIDE PINS: PASSIVATI 4. ELECTRICAL PROPERTIES (API a) DIELECTRIC STRENGTH:	PLIES TO HOUSING ONLY 1,000 VOLTS RMS AT SE	A LEVEL;			JA
	b) INSULATION RESISTANC 5. ENVIRONMENTAL PROPERTIN OPERATING TEMPERATUR 6. RF CABLE ASSY SPECIFICATIO a) IMPEDANCE 50 OHMS. b) HI-POT & CONTINUITY c) PKZ [®] SPECIFICATIONS P d) FREQUENCY: DC TO 6 G	ES: RE: -40° F TO +194° F (-40 NS: TEST 100%. ER IDS-156.	M.			
С						
A					CABLE ASSEMBLY (23X) SEE NOTE 6	5 CABLE
В						(39.8
_						(33.0
А			RELEASED PER ECN 14504	3/28/2025 AH	WARNING - THIS DOCUMENT CONTAINS TECHNICAL DATA WHOSE EXPORT IS RESTRICTED BY THE ARMS EXPORT CONTRO ACT (TITLE 22, U.S.C., SEC 2751, ET. SEQ.) O THE EXPORT ADMINISTRATION ACT OF 197 AS AMENDED, TITLE 50, U.S.C., APP 2401 ET SEQ. VIOLATIONS OF THESE EXPORT LAWS SUBJECT TO SEVERE CRIMINAL PENALTIES. DISSEMINATE IN ACCORDANCE WITH PROVISIONS OF DOD DIRECTIVE 5230.25. This drawing embodies a propried design of The Phoenix Company Chicago, Inc., Naugatuck, CT 06 All design, manufacturing, reproduction, use, sale, and other rights regarding the same are expressly reserved. The information this drawing may be covered completely or in part by patents and/or patents pending.	R UNLESS OT P, SPECI PAL WORKM, ARE STANDARI DIMENSI INCHES OR DO NOT PRIM TOLERANCE: FRACTIONS: DECIMALS: . . ANGLES: ± 1
Į	4	REV.	DESCRIPTION	JZCO/ZUZS AH DATE APPROVAL 3	-	

